



## 5. Childproof Lid

The Evergreen comes with one long screw which can be used to secure the lid in place. There is a small opening, a recess, which is the point of fixing the screw through the lid and inner raised lip of the main body of the tank. See picture below.



The Evergreen has 1 interconnection / draindown point near the base. It is possible to connect two Evergreen Tanks together. Please use the 3P Tank to Tank Connection Kit.

## Instructions



We recommend using the 3P Filter Collector Universal to fill the Evergreen.

Where the water butt cannot be located within 30 cm of the down pipe, longer Universal Long Link Kits are available online (Art. No. 9000123U to U5).

The Evergreen has a 3/4" brass threaded port to connect the 3/4" brass tap that comes with the Evergreen.

If in any doubt during installation, please consult a professional tradesperson.





### 1. Setting up

Site the Evergreen on a firm, level surface, adjacent to the downpipe.

Refer to your Filter Collector or other rain diverter instructions.



### 2. Connection to the Downpipe

Measure carefully across from the downpipe to the Evergreen when connecting the Filter Collector and mark the entry point for the Filter.

Use the 32 mm drill bit provided in the kit to drill the hole.



### 3. Connecting the Tap

Screw the 3/4" Brass High Flow Tap provided with the Evergreen into the 3/4" BSP thread located 30 cm above the Tank base.. Other 3/4" taps or fittings can be used. Use PTFE tape when installing the tap for protection against leaks, and to make sure the tap sits in an upright position.

### 4. Winter Care Precautions

To minimise the risk of any damage being caused, the Evergreen must be drained completely and disconnected from the rainwater inlet during freezing weather conditions.



**Filter Collector Universal: Art. No.: 2000840U**

Available in 4 colours to suit your downpipe

